

**This Page Is Inserted by IFW Operations  
and is not a part of the Official Record**

## **BEST AVAILABLE IMAGES**

**Defective images within this document are accurate representations of  
the original documents submitted by the applicant.**

**Defects in the images may include (but are not limited to):**

- **BLACK BORDERS**
- **TEXT CUT OFF AT TOP, BOTTOM OR SIDES**
- **FADED TEXT**
- **ILLEGIBLE TEXT**
- **SKEWED/SLANTED IMAGES**
- **COLORED PHOTOS**
- **BLACK OR VERY BLACK AND WHITE DARK PHOTOS**
- **GRAY SCALE DOCUMENTS**

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

# EUROPEAN PATENT OFFICE

## Patent Abstracts of Japan

PUBLICATION NUMBER : 09229909  
PUBLICATION DATE : 05-09-97


APPLICATION DATE : 26-02-96  
APPLICATION NUMBER : 08038351

APPLICANT : HITACHI CONSTR MACH CO LTD;

INVENTOR : TAKISHITA YOSHIHIKO;

INT.CL. : G01N 29/04 G01N 21/89 G01N 23/18  
G01N 27/82

TITLE : METHOD AND DEVICE FOR  
INSPECTING MOVING OBJECT TO BE  
INSPECTED



ABSTRACT : PROBLEM TO BE SOLVED: To provide a method and device for inspecting moving object wherein detailed information on defects of a moving object to be inspected is obtained and the reliability of inspection is improved by preventing erroneous judgement.

SOLUTION: An object to be inspected 3 is wound from an uncoiler 1 to a coiler 2 and, during this period, inspected with ultrasonic wave with no focus irradiated from a probe 40a of an ultrasonic wave flaw detector 40. When a defect is found, a control part 60 stops driving of the object 3, and after retracing the object 3 to a defect position, detailed information about defect is collected and recorded in a recorder 8 with the use of ultrasonic wave having a focus which is radiated from a probe 40b together with a supporting mechanism 10 which allows the ultrasonic wave to scan the object 3. When this is done, the object 3 is moved again, and when defective part comes to a marking device 7, the control part 60 instructs the marking device 7 to give a mark on the part.

COPYRIGHT: (C)1997,JPO